

2MP Starlight Turret - Fixed Lens IP Camera NP-C-T2E30-28(-B)(40)



- Turret Camera Style
 - 1920x1080@30fps Resolution
 - 2.88mm/4mm Lens Size
 - Up to 30m (98ft) IR Range
 - IP67 Outdoor Rating
 - Motion Detection
 - H.264 Encryption
 - White/Black
-



Left View



Right View

Technical Specifications

Camera	NP-C-T2E30-28			NP-C-T2E30-40		
Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS					
Lens	2.8mm@F1.6			4.0mm@F1.6		
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognise (m)	Identify (m)	
	2.8	42	16.8	8.4	4.2	
	4	60	24	12	6	
Angle of view (H)	112.7°		86.5°			
Angle of View (V)	60.1°		44.1°			
Angle of View (O)	146.5°		106.4°			
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 80°		Rotate: 0° ~ 360°	
Shutter	Auto/Manual, 1 ~ 1/100000s					
Minimum Illumination	Colour: 0.002Lux (F1.6, AGC ON)					
	0Lux with IR					
Day/Night	IR-cut filter with auto switch (ICR)					
Digital noise reduction	2D/3D DNR					
S/N	>52dB					
IR Range	Up to 30m (98ft) IR range					
WDR	DWDR					
Video						
Video Compression	Ultra 265, H.265, H.264					
H.264 code profile	Baseline profile, Main Profile, High Profile					
Frame Rate	Main Stream: 2MP (1920*1080), Max 30fps;					
	Sub Stream: 4CIF (704*576), Max 30fps					
	Third Stream: CIF (352*288), Max 30fps					
HLC	Supported					
BLC	Supported					
OSD	Up to 8 OSDs					
Privacy Mask	Up to 4 areas					
ROI	Up to 8 areas					
Motion Detection	Up to 4 areas					

Technical Specifications

Network	
Protocols	IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP
Compatible Integration	ONVIF (Profile S, Profile T), API
Interface	
Network	10/100M Base-TX Ethernet
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 4.5W
Dimensions (Ø x H)	Φ118 x 96mm (Φ4.6" x 3.8")
Weight	0.3kg (0.44lb)
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Ingress Protection	IP67

Dimensions

