

8MP Turret - Fixed Lens IP Camera

NP-C-T8E30-28(-B)(40)



- Turret Camera Style
- 3840x2160@20fps Resolution
- 2.8mm/4mm Lens Size
- Up to 30m (98ft) IR Range
- IP67 Outdoor Rating
- Motion Detection
- Ultra H.265 Encryption
- White/Black (2.8mm)



Front View



Side View

Technical Specifications

Camera	NP-C-T8E30-28			NP-C-T8E30-40		
Sensor	1/3", 8.0 megapixel, progressive scan, CMOS					
Lens	2.8mm@F2.0			4.0mm@F2.0		
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognise (m)	Identify (m)	
	2.8	84	33.6	16.8	8.4	
	4	120	48	24	12	
Angle of view (H)	112.7°		86.5°			
Angle of View (V)	60.1°		44.1°			
Angle of View (O)	146.5°		106.4°			
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 80°		Rotate: 0° ~ 360°	
Shutter	Auto/Manual, 1-1/100000 s					
Minimum Illumination	Colour: 0.05 Lux (2.0, AGC ON)					
	0Lux with IR					
Day/Night	IR-cut filter with auto switch (ICR)					
Digital noise reduction	2D/3D DNR					
S/N	>56dB					
IR Range	Up to 30m (98ft) IR range					
Defog	Digital Defog					
WDR	120dB					
Video						
Video Compression	Ultra 265, H.265, H.264, MJPEG					
H.264 code profile	Baseline profile, Main Profile					
Frame Rate	Main Stream: 8MP (3840*2160): Max. 20 fps;5MP(2944*1656): Max. 30 fps; 4MP(2560*1440): Max. 30 fps; 2MP(1920*1080): Max. 30 fps					
	Sub Stream:720P (1280*720): Max. 20 fps					
	Third Stream:4CIF (704*576): Max. 20fps					
HLC	Supported					
BLC	Supported					
OSD	Up to 4 OSDs					
Privacy Mask	Up to 4 areas					
ROI	Up to 2 areas					
Motion Detection	Up to 4 areas					

Technical Specifications

Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Interface	
Network	10/100M Base-TX Ethernet
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 5W
Dimensions (Ø x H)	Φ118 x 96mm (Ø4.6" x 3.8")
Weight	0.33kg (0.99lb)
Working Environment	-30°C - +60°C (-22°F - C121 140°F), Humidity: ≤95% RH(non-condensing)
Ingress Protection	IP67

Dimensions

