

4MP Starlight Mini Anti-Vandal Dome - Fixed Lens IP Camera

NP-C-DM4P15-MS-28(B)



- Mini Anti-Vandal Dome Camera Style
 - 2592x1520@20fps Resolution
 - 2.8mm Fixed Lens
 - Up to 15m (49ft) IR Range
 - IP66 Outdoor Rating
 - IK10 Impact Rating
 - Motion Detection
 - Ultra 265, H.264, MJPEG
-



Left View



Right View

Technical Specifications

Camera	NP-C-DM4P15-MS-28(B)					
Sensor	1/3", 4.0 megapixel, progressive scan, CMOS					
Lens	2.8mm@F2.0					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognise (m)	Identify (m)	
	2.8	63	25.2	12.6	6.3	
	3.6	81	32.4	16.2	8.1	
Angle of view (H)	104.4°					
Angle of View (V)	54.4°					
Angle of View (O)	135.7°					
Adjustment angle	Pan: 0° ~ 90°		Tilt: 0° ~ 65°		Rotate: 0° ~ 360°	
Shutter	Auto/Manual, 1 ~ 1/100000s					
Minimum Illumination	Colour: 0.03Lux (F2.0, AGC ON)					
	0Lux with IR					
Day/Night	IR-cut filter with auto switch (ICR)					
Digital noise reduction	2D/3D DNR					
S/N	≥55 dB					
IR Range	Up to 15m (49ft) IR Range					
Defog	Digital Defog					
WDR	120dB					
Video						
Video Compression	Ultra 265, H.264, MJPEG					
H.264 code profile	Baseline profile, Main Profile, High Profile					
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps; 4MP (2560*1440), Max 25fps; 3MP (2048*1520), Max 30fps;					
	Sub Stream: 2MP (1920*1080), Max 30fps;					
	Third Stream: D1 (720*576), Max 30fps					
9:16 Corridor Format	Supported					
HLC	Supported					
BLC	Supported					
OSD	Up to 8 OSDs					
Privacy Mask	Up to 8 areas					
ROI	Up to 8 areas					
Motion Detection	Up to 4 areas					

Technical Specifications

Audio	
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, Up to 256GB
Network Storage	ANR
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Interface	
Audio I/O	Audio cable
	Input: impedance 35kΩ; amplitude 2V [p-p]
	Output: impedance 600Ω; amplitude 2V [p-p]
Built-in Mic	Supported
Network	1 RJ45 10M/100M Base-TX Ethernet
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 4.5W
Dimensions (Ø x H)	110mm x 61mm (4.3" x 2.4")
Weight	0.25kg (0.55lb)
Working Environment	-35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Ingress Protection	IP66
Impact Rating	IK10

Dimensions

