

4 Channel, 8MP PoE Network Video Recorder NP-R-NVRP104-4P-4K



- 4 PoE, 100Mbps Channels
- 3840x2160@30fps Playback
- 8-ch Synchronous Playback
- 1 SATA, Up to 10TB
- Simultaneous HDMI & VGA Output
- Supports Cloud Firmware Upgrades
- 1-ch HDMI, 1-ch VGA Outputs
- 1 10M/100M RJ45 Ethernet Interface
- 2 USB2.0 Ports
- ONVIF Support
- Ultra 265/H.265/H.264 Support
- Black Colour



Left View



Side View

Technical Specifications

Recorder	NP-R-NVRP104-4P-4K
IP Video Input	4 Channels
Network	
Incoming Bandwidth	64Mbps
Outgoing Bandwidth	64Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI Output	3840x2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Recording Resolution	8MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-Ch, RCA
Synchronous Playback	4 Channels
Corridor Mode Screen	3/4
Decoding	
Decoding Format	Ultra 265/H.265/H.264
Liveview/Playback	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	2x8MP@30 3x5MP@30 4x4MP@30 5x3MP@30 8x2MP@30 16x1MP@30
Hard Disk	
SATA	1 SATA Interface
Capacity	Up to 10TB per Disk
External Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 1 x USB2.0, 1 x USB3.0
Supported Standard	IEEE 802.3at, IEEE 802.3af
Interface	4 independent 100 Mbps PoE network interfaces
Max Power	Max 30W for single port Max 54W in total (13.5W for each)

General	
Power Supply	48V DC
Power Consumption	≤9 W (without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F) Humidity ≤ 90% RH (non-condensing)
Dimensions (WxDxH)	260mm × 240mm × 46mm (10.2"×9.4"×1.8")
Weight (W/out HDD)	1kg (2.20 lb)

Dimensions

