

16 Channel, 8MP PoE Network Video Recorder NP-R-NVRP216-16P-4K



- 16 PoE Channels
- 3840x2160@30fps Playback
- 16-ch Synchronous Playback
- 2 SATAs, Up to 16TB
- Simultaneous HDMI & VGA Output
- Supports Cloud Firmware Upgrades

- 1-ch HDMI, 1-ch VGA Outputs
- 1 Gigabit RJ45 Ethernet Interface
- 2 USB2.0 Ports
- 4 Alarm inputs, 1 alarm output
- ONVIF Support
- Ultra 265/H.265/H.264 Support
- Black Colour



Front View



Side View

Technical Specifications

Recorder	NP-R-NVRP216-16P-4K
IP Video Input	16 Channels
Two-way Audio Input	1-Ch, RCA
Network	
Incoming Bandwidth	112Mbps
Outgoing Bandwidth	96Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI Output	4k(3840x2160@30) / 4k(3840x2160@60) / 1024X768@60 / 1280X720@60 / 1280X1024@60 / 1920X1080@50 / 1920X1080@60
VGA Output	1024X768@60 / 1280X720@60 / 1280X1024@60 / 1920X1080@50 / 1920X1080@60
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-Ch, RCA
Synchronous Playback	16 Channels
Corridor Mode Screen	3/4/5/7/9/10/12/16
Decoding	
Decoding Format	Ultra 265/H.265/H.264
Liveview/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	1x 8MP@30fps 2x 4MP@30fps 3x 3MP@25fps 4x 2MP@30fps 8x 1MP@30fps 16x D1
Hard Disk	
SATA	2 SATA Interface
Capacity	Up to 8TB per Disk
External Interface	
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB2.0
Supported Standard	IEEE 802.3af/at
Interface	16 independent 100Mbps PoE network interfaces
Max Power	Max 30W for single port Max 240W in total (15W for each)
Alarm In	4 Channels
Alarm Out	1 Channel

General	
Power Supply	220V AC
Power Consumption	≤9 W (without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)
Dimensions (WxDxH)	380mm × 315mm × 49.1mm(15.0" × 12.4" × 1.9")
Weight (W/out HDD)	2.4kg (5.29 lb)

Dimensions

